

SPECTRAJET ARCHIVAL MATT 230gsm

SPECIAL-COATED MATT PAPER

PRODUCT SPECIFICATION *

Weight DIN EN ISO 536	g/m ²	229	± 7
Thickness DIN EN ISO 534	µm	270	± 8
	mil	10.6	± 0.3
Colour Elrepho UVO (D65) ISO 2469	L	95,8	± 1,0
	a	-0,2	± 0,5
	b	-1,2	± 1,0
	delta b	12,3	± 0,8
CIE whiteness (D65/10°) min. ISO 2469		> 134	
Opacity min. ISO 2469	%	> 86	

BENEFITS & PROPERTIES

- Fine art look and feel
- Pin-sharp details
- Vivid colours
- High colour consistency and gamut
- High opacity
- High light fastness
- Meets criteria for permanence according ISO 9706
- Certified by Fogra

KEY APPLICATIONS

Photo Retail

- Black and white photography
- Fine art photo and panorama prints
- Fine art greeting cards

Directions for use

Store material only in original packaging under normal climatic conditions (23°C, 50 % RH). Protect material from direct sunlight. It is recommended to adapt the material to indoor climate at least 24 hours before usage.

* Modifications reserved.

Printability

Simplex printable

Laminatability

Hot & cold

Printing Technology

• Inkjet water-based

Compatibility

Can be used on all commercial Inkjet Minilab Printsystems like Noritsu, Fuji and Epson

Certificates



Paper Aging (ISO 9706) | 29319

Fogra 29319